

INSULATING STICKS FOR SUBSTATION USE

Telescopic sticks for voltage detectors and earthing systems for use in dry and wet conditions

Telescopic stick contains 2 elements made of resin polyester/glass fiber foam filled tube, which slide together and are equipped with a push button lock.

Product Number	Rated Insulation (kV)	Ø (mm)	Overall Length (m)		Weight (kg)
			Folded	Extended	
CE-4-21*	90	41/32	1.15	2	1.5
* Add end-piece C, K or E					

Fixed length stick for use in dry and wet conditions

Manufactured from 36 mm dia. elements, with single 100 dia. skirts, light and rigid, shock resistant.

Product Number	Rated Insulation (kV)	Ø (mm)	Overall Length (m)	Weight (kg)
CF-5-40*	40	36	1.5	1.15
* Add end-piece C, K or E				

Standard stick for use in dry conditions

Product Number	Rated Insulation (kV)	Ø (mm)	Overall Length (m)	Weight (kg)
CF-3-72*	72.5	36	1.5	0.88
* Add end-piece C, K or E				

Short length clamp stick

Product Number	Ø (mm)	Overall Length (m)	Weight (kg)
MG-115/1-S	32	1.5	2.4

Rescue stick

Product Number	Ø (mm)	Overall Length (m)	Weight (kg)
CS-45	45	1.65	1

