


**MT-731**

**MT-732**

**MT-734**


**MT-735**

**MT-737-H**

**MT-732-A**

**MT-732-B**

**MT-732-E**

**MT-732-H**

**MT-734**

**MT-734-A**

**MT-734-B**

**MT-734-E**

**MT-734-H**
**MT-731-A**
**MT-731-B**
**MT-731-E**
**MT-731-H**
**MT-735**
**MT-735-A**
**MT-735-B**
**MT-735-E**
**MT-735-H**

### HV AND EHV CLAMPS MANOEUVRABLE BY INSULATING STICK

Body in aluminium alloy with trapezoidal threaded screw. Interposed elastic washers in the clamping system improve efficiency and insure a higher withstand in case of electrodynamic shock. Manoeuvring by CM-6 insulated stick of appropriate length and characteristics.

Product Number	Clamping Capacity (Ø mm)	Test Current (kA/1s)	Copper Connection			Weight (Kg)	Dimensions (mm) h x L x thickness
			Copper Cables (mm² max.)	Contact Range Width (mm)	Stud or Hole		
<b>MT-731*</b>	5-60	40	150	45	M 12	1.45	200 x 200 x 50
<b>MT-732*</b>	40-120	40	150	45	M 12	1.45	200 x 200 x 50
<b>MT-734*</b>	5-40	40	150	40	M 12	0.8	145 x 125 x 52
<b>MT-735*</b>	15-60	40	150	40	M 12	0.8	195 x 135 x 45
<b>MT-737*</b>	20-120	40	150	40	M 12	1.35	340 x 200 x 55

\* Add type of connection A - B - E - H