

## PIRANHA SERIES



PHS2-6-50



PHS2-35-185

### PIRANHA™ SERIES—IN-LINE SPLICE WATERPROOF, FULLY INSULATED PIERCING CONNECTOR

#### APPLICATION


For the waterproof splicing or jointing of two cables.

#### CABLE TYPES\*

- This versatile connector accommodates a vast array of insulated cable types, sizes and constructions in any combination;
- + circular aluminium or copper
  - + stranded or solid
  - + single or double insulated
  - + LVABC

#### FEATURES

- + waterproof to IP67 equivalent
- + fully insulated. No exposed live components
- + centre barrier for positive cable core positioning
- + torque controlling shear head bolts for correct contact pressure
- + insulation piercing on both sides of the connector
- + no need to strip cable
- + no resins or heat shrink required
- + flexible sealing cable ports that are not affected by the angle of cable entry
- + fitted with push-on protective bolt caps



PHS2 series connector in-line splice configuration.

#### TESTING SPECIFICATIONS

Contact Sicame for details

Product Number	Copper				Aluminium			
	Single Insulation		Double Insulation		Single Insulation		Double Insulation	
	Min	Max	Min	Max	Min	Max	Min	Max
PHS2-6-50	6	50	6	50	6	50	6	50
PHS2-35-185	35	150	35	150	35	150	35	150

\*Cable types and ranges are nominal and indicative only. Suitability of cable type and size should be confirmed with Sicame prior to application.